128 U. S. MERCHANT, OCEAN STATION VESSELS (OSV'S) SPECIAL SHIPS SURFACE MARINE SYNOPTIC OBSERVATIONS

AREA COVERAGE

World-wide marine areas.

PERTOD OF RECORD

July 1963 - U. S. Ships

The following have been received through international exchange:

January 1962 - Canadian OSV "P"

January 1962 - British OSV's "A". "I". "J"

August 1959 - Norwegian OSV "M"

Data will be added from foreign sources. Similar data for prior periods are in Decks 116, 117.

#### OBSERVATION TIME

GMT. Three or six-hourly synoptic hours 00, 03, 06, 09, 12, 15, 18, 21.

WMO. Modified for the international marine card according to WMO specifications.

#### SOURCE

- 1. USWB Forms 615-5 revised. IISWB Forms WBAN 11 B. USWB Forms 615-4 (Great Lake Ships) OPNAV Form 3144-1
- 2. Cards or cards punched from forms received from foreign countries at the NWRC.

#### MISSING DATA

When an element(s) is missing, the appropriate columns are left blank.

#### COLUMNS AND ELEMENTS PUNCHED

Columns 1-51, 53-57, 59-63 and 74-76 were punched for international exchange. (Additional data are punched for U. S. data sources in Columns 64-73, and 77-80, when data are available.) (Columns 52, 58, 64-73, and 77-80 are left blank for international exchange.)

#### The elements punched are:

Type of low cloud

Height of lower cloud in code

Total Cloud Amount in eights	Type of middle cloud	x Ships Direction and Speed
Wind Direction	Type of high cloud	x Pressure Tendency and
Wind Speed	Sea Temperature	Amount of Change during
Visibility	*Air-Sea Temperature Differences	the past 3 hours
Present Weather	Wave Direction	x Ice Accretion Type, Thick-
Past Weather	Wave Period > Sea	ness, and Rate
Sea Level Pressure in Millibars	Wave Height	x Significant Cloud Data
Temperature, Air	Wave Direction	x Ice field presence
Temperature, Wet bulb	Wave Period Swell	*Temperature Dew point
Total amount of low clouds in eighths	Wave Height	<u>•</u> · · · · · · · ·

#### ADDITIONAL REMARKS

Punching practices for columns 1, 61-73 changed from time to time. These changes are described in the card contents. Future punching changes will be added as an addendum.


#### CORRECTIONS

Any errors in this manual should be called to the attention of Director, National Weather Records Center, or Chief, Data Processing Division, Climatic Center, USAF. Please give specific instances of error, and correct information if available.

x Indicates the element was not included in cards for international exchange. \*See card content Page 3.

Code Indicators

## REFERENCE MANUAL



90									99
80									
70									
60									
50									
40								·	
30									
20									
10	П	12	13	14	15	16	17	20	19
00	Oi	02	03	04	05	06	07	80	09

3	4
1	2

SOUARES ARE ALWAYS ORIENTED
SO THAT THE LOWEST NUMBER IS
NEAREST THE INTERSECTION OF
THE GREENWICH MERIDIAN AND
THE EQUATOR

Issue Date: 28 May 65

Page 2

CARD CONTENT						
Column	Item or Element	Symbolic Letter	Card Code	Card Code Definition	Remarks	
1,8- 80	Missing Data X Overpunch		BlankX/	Indicates an "11" overpunch	May only be punched in cols. 18, 20, 32, 35, 37, ‡, 43, 46, 64 and 74. (See cols. 39, 40-42, 51)	
1	Temp. Indicator		<del>1</del>	Temps. in 0.1°C Temps. in whole °C.	The 0.1° Cols. 34, 37, 45, 48, 76 are punched "O" when reported to whole °C.	
2-3	Year		62-	1962-	Last two digits of year.	
4-5	Month		01-12	JanDec.	Date is punched in GMT	
6-7	Day	YY	01-31	Day of month		
8	Octant	Q	1-3, 5-8	Code 1, Page 5		
9-11	Latitude	L <sub>a</sub> L <sub>a</sub> L <sub>a</sub>	000-900	00.0-90.0° Latitude	North or South indicated by Col. 8. East or West (the hundreds	
12-14	Longitude	r°r°r°	000- <u>900</u> _	00.0-90.0° Longitude 90.1-180.0° Longitude	digit of Longitude is cmitted) indicated by Col. 8.	
15-16	Hour (GMT)	GG	00-23	'00-23 GMT nearest whole hour	3 or 6 hourly observations	
17	Total Cloud	N	0-9	Code 2, Page 5		
18-19		dd	00-36	Code 3, Page 5	"X" overpunch in Col. 18 indi- cates wind was measured.	
20-21	Wind Speed	ff	0-35 T	Calm-99 Knots 100 through 199 Knots.	X overpunch in Col. 20 equal to or greater than 100 Knots.	
22-23	Visibility	vv	90-99	Code 4, Page 5 observed in nautical miles	Some cards from a foreign country source may be in the 00-89 code. See Code 3A Page 5 for conversion.	
24-25	Present Weather	ww	00-99	Code 5, Pages 6 and 7	Highest applicable code is	
26	Past Weather	W	0-9	Code 6, Page 7	Past weather for 6 hours for 00, 06, 12, 18Z observations. Past weather for 3 hours for 03, 09, 15, 21Z observations.	
27-31	Pressure Corrected to MSL	PPPPP	07000- 10999	700.0 -1099.9 Mbs.	When reported in whole Mbs. "O" is punched in Col. 31.	
32-34	Air Tempera- ture	iliti	$\frac{x}{0}$ 01- $\frac{x}{9}$ 99	0.0° through +99.9°C. -0.1° through -99.9°C		
35-37	Wet Bulb Temperature	TITwet		Same Card Code as Cols. 32-34.	In whole degrees telsius.  Negative temperatures are indicated by an "X" overpunch in Col. 32 or 35.  Ice on wet bulb is indicated by an "X" overpunch in Col. 37.	
38-42	Clouds				Criteria for the Specifications are in the International Cloud Atlas.	
38 -	Total Amount of Lower	N <sub>h</sub>	0-9	Code 1, Page 5	Amount of the celestial dome covered by Type C <sub>L</sub> (or Type C <sub>M</sub>	
<del>3</del> 9	Low Type	c <sub>L</sub>	<del> </del> <del>0-9</del>	Code 7, Page 7 *	when C <sub>L</sub> is not present.  The most significant type of C <sub>L</sub> cloud is reported.	

			Ċ	ARD CONTENT	
Column	Item or Element	Symbolic Letter	Card Cade	Card Code Definition	Remarks
40	Height of Lower	h	0-9 X	Code 8, Page 7	The height of the lowest cloud present or $C_L$ (or $C_M$ when there are not any $C_L$ ) (that is the
<b>4</b> 1 -	Middle Type	c	ō-9	Code 9, Fage 7	smallest visible fragment. The most significant type of $\overline{c}_{M}$ .
¥2¯¯	High Type	C <sub>H</sub>	ō-9 x	Code 10, Page 7 *	The most significant type of CH.
43-45	Sea Tempera- ture	TTT		Same code as Cols. 32-34	"X" overpunch in Col. 43 indicate negative values.  If all temperatures are reported to 0.1° C except Sea Temperature, this does not make code punch "1" in Col. 1 illegal.
46-48	Air-Sea Temperature Differences			Same code as Cols. 32-34	"X" overpunch in Col. 46 indicates the Sea Temperature is higher than the Air Temperature.
		-			These columns were not punched beginning Jan. 1965 (except when prepared for international exchange.
49-54	Wind Waves (Sea)				Waves resulting from local wind influence.
49-50	Direction	d <sub>w</sub> d <sub>w</sub>	00-36	Code 11, Page 8	Direction is decoded to 36 points when dwdw is reported with 50
<del>-</del> ,		- <b>-</b> ,	<sup>49</sup> ō-ō,⁻x⁻ ⁻	Code 12, Page 8	added. Code 99 is decoded to 49. These values are adjusted in H.H. Cols. 53-54. Punched as coded. U.S. is
51 -	Period Blank	P <sub>w</sub>		Not Punched	using the X code.
<u>5</u> 2 <u> </u>	Height	- # <sub>#</sub> ,	Blank 00 01-99	Less than 1/4 meter 1/2 through 49 1/2 meters.	Punched in 1/2 meter units. Decoded from WMO Code. (See Code 13, Page 8.) and remarks on original records. See remarks in cols. 49-50.
<u>55-60</u>				Same Code as Cols. 49-54 respectively	Waves caused by other than local wind influence.
55-56 57	Direction Period				
58 59-60	Blank Height	<u>x</u>			
61-62	Country Number		00-99	Code 14, Page 8	See Appendix for in house (NWRC) uses for Cols. 61-73, 77-80.
<u>6</u> 3	Code Indicator		0 ,	Indicates Codes used in card are WMO Codes effective in year punched in cols. 2-3.	These Cols. are blank for international exchange.
64-73	Blank			See Remarks	
-				·	

<sup>\*</sup> X punch of code was generally discontinued beginning November 1963 on cards from U. S. Sources.

	CARD CONTENT							
Column	Item or Element	Symbolic Letter	Card Code	Card Code Definition	Romarks			
74-76	Dew point Temperature	T <sub>d</sub> T <sub>d</sub> T <sub>d</sub>		Same Code as Cols. 32-34.	Negative dew point temperature is indicated by an X overpunch in Col. 74. (Note - Not punched in cards at NWRC beginning Jan. 1965.) Dew points are computed and punched for international exchange.			
7-80	Blank				See remarks columns 61-62.			
		·	·					
				·				
		1						

Neuticel

Miles

Hiles

### CODE TABLES

#### CODE TABLES

When coding a meteorological report, symbolic letters are replaced by figures, which specify the value or the state of the corresponding element. In some cases, the state of the corresponding element. In some cases, the specification of the symbolic letter (or group of letters) is sufficient to permit a direct transcription into figures (e.g., GG or PPP). In other cases, these figures are ob-tained by means of a special code table (or code, in short)

The codes elaborated to this end, as far as they are in world-wide use, are called international meteorological code tables. These same codes are used inversely for decoding observations and thus making available the information contained in them.

Besides the specifications given by the code tables in world-wide use, other sets of code tables are established by the WMO for regional use. Further arbitrary codes have been made necessary by the use of data in card decks which were never encoded into WMO forms.

Only codes pertinent to this card deck are included in the present manual. They appear in the order in which the elements were introduced in the description of the car content. They are numbered consecutively, and if applicable, the corresponding MMC code numbers are shown.

### Code 2 (1949 WMO Code 60) (1960 WMO Code 2700)

- N The fraction of the celestial dome covered by cloud
- Nh The fraction of the celestial dome covered by the cloud(s) reported for C, or, if no C -cloud present, for C

#### Code figure

_		•
0	0	0
1	l okta or less, but	1/10 or less, but not 🔨
	not zero	zero
2	2 oktas	2/10 - 3/10
3	3 oktas	4/10
ű,	4 oktas	5/10
5	5 oktas	6/10
6	6 oktas	7/10 - 8/10
7	7 oktas or more, but	9/10 or more, but not 10/10
	not 8 oktas	
А	8 oktos	10/10

Sky obscured, or cloud

amount cannot be

1750 - 1840

estimated

## Code 3

(1949 WMO Code 23) (1960 WMO Code 0877)

dd - True direction, in tens of degrees, from which wind is blowing (or will blow)

Code figure		Code figure	
00	Celm	19`	185° - 194°
01	5° - 14°	20	195° - 204°
02	15° - 24°	21	205° - 214°
03	25° - 34°	22	215° - 224°
04	35° - 44°	23	225° - 234°
05	45° - 54°	24	235° - 244°
06	55° - 64°	25	245° - 254°
07	65° - 74°	26	255° - 264°
08	75° - 84°	27	265° - 274°
09	85° - 94°	28	275° - 284°
10	95° - 104°	29	265° - 294°
11	105° - 114°	30	295° - 304°
12	115° - 124°	31.	305° - 314°
13	125° - 134°	32	315° - 324°
14	135° - 144°	33	325° - 334°
15	145° - 154°	34	335° - 344°
16	155° - 164°	35	345° - 354°
17	165° - 174°	36	355° - 4°

## Code 3A

Conversion Table of Visibility for Nautical Miles from the 00-89 code to 90-99 decade

1949 00-89 Code	1949 & 1955 Decade 90-99	1955 & 1960 = 00-89 <u>Code</u>	Code 90-99 Nautical Mile <u>Values</u>
X0-X2	90	00	< 50 yards or meters
x3-x9, 00	91	01	50 yards or meters
01	92	02-04	200 yards or meters
02-03	93	05-08	1/4 or 500 meters
04-08	94	09-17	1/2
09-17	95	18-36	1.0
18-45	96	37-58	2.0
46-80	97	59-68	5.0
81.	·98	69-82	10.0
81 82-89	99	83-89	>25.0

When distances are between two of the distances assigned to the above codes the code figure for the smaller distance are reported and punched.

### Code 4 (1955 WMO Code 84) (1960 WMO Code 4377)

VV - Horizontal visibility at surface

Code figure         Km         (Approx.)         (Ap				Statute	Nautical
OO         <0.1         <110         <1/16         <1/16           01         0.1         110         1/16         1/16           02         0.2         220         1/8         1/8           03         0.3         330         3/16         3/16           04         0.4         440         1/4           05         0.5         550         5/16         1/4           06         0.6         660         3/8         5/16           07         0.7         770         7/16         3/8           09         0.9         990         9/16         1/2           100         1         1,100         5/8         1/2           09         0.9         990         9/16         1/2           100         1         1,100         5/8         1/2           11         1.1         1,200         3/4         5/8           12         1.2         1,200         3/4         5/8           13         1.3         1,430         13/16         3/4           14         1.4         1,540         7/8         3/4           15         1.5         1,650 <td>Code</td> <td></td> <td>Yards</td> <td>Hiles</td> <td>Miles</td>	Code		Yards	Hiles	Miles
01	figure	Km.	(Approx.)	(Approx.)	(Approx.)
01	00	<0.1	<110	<1/16	< 1/16
02				1/16	1/16 🔪
0h         0.4         th0         1/h           05         0.5         550         5/16         1/h           06         0.6         660         3/8         5/16           07         0.7         770         7/16         3/8           08         0.8         880         1/2         2           09         0.9         990         9/16         1/2           100         1         1,100         5/8         1/2           11         1.1         1,210         11/16         1           12         1.2         1,230         3/h         5/8           13         1.3         1,530         13/16         1           12         1.2         1,230         13/h         5/8           13         1.3         1,530         13/16         1           15         1.5         1,650         15/16         1         7/8           15         1.5         1,650         15/16         1         7/8         1           17         1.7         1,760         1         1/16         1         1         1         1         1         1         1         1 <td></td> <td></td> <td></td> <td>1/8</td> <td>1/8</td>				1/8	1/8
05	03 ·	0.3	330	3/16	3/16
06         0.6         660         3/8         5/16           07         0.7         770         7/16         3/8           08         0.8         880         1/2         99           09         0.9         990         9/16         1/2           10         1         1,100         5/8         11           11         1.1         1,210         3/4         5/8           12         1.2         1,220         3/4         5/8           13         1.3         1,430         13/16         3/4           14         1.4         1.4         1,540         7/8         3/4           15         1.5         1,560         15/16         7/8           16         1.6         1,760         1         1/16         1           18         1.8         1,980         1         1/8         1           19         1.9         2,090         1         3/16         1           20         2.2         2,200         1         1/16         1           21         2.1         2,310         1         5/16         1         1/8           23         2.			- 440	1/4	
07	05	0.5	550	5/16	1/4
08	<u>06</u>	0.6	660	3/8	5/16
10 1 1,100 5/8 11 1.1 1,210 11/16 12 1.2 1,220 3/k 5/8 13 1.3 1,3 1,430 13/16 14 1.4 1,540 7/8 3/4 15 1.5 1,550 15/16 7 16 1.6 1,760 1 1/16 18 1.8 1,980 1 1/8 1 19 1.9 2,090 1 3/16 20 2 2,200 1 1/8 21 2.1 2,310 1 5/16 1 22 2.2 2,420 1 3/8 23 2.3 2,530 1 7/16 1 1/4 24 2.4 2,640 1 1/2 25 2.5 2,750 1 9/16 1 3/8 26 2.6 2,860 1 5/8 27 2.7 2,970 1 11/16 28 2.8 3,080 1 3/4 1 1/2 29 2.9 3,190 1 13/16 30 3 3,3100 1 13/16 30 3 3,300 1 7/8 1 5/8 31 3.1 3,410 1 15/16 32 3.2 3,520 2 1 3/8 33 3.2 3,520 2 1/16 34 3.4 3,74 3,740 2 1/16 35 3.5 3,850 2 1/16 36 3.6 3,960 2 1/16 37 3.7 4,070 2 5/16 2 38 3.8 4,180 2 3/8 39 3.9 4,280 2 5/16 1 41 4.1 4,510 2 9/16 42 4.2 4,600 2 1/2 43 4.3 4,3 4,730 2 1/26 44 4,400 2 1/2 45 2/6 2 6,600 2 1/26 46 4,500 2 5/8 2 1/46 47 3,4 3,4 4,700 2 5/16 2 48 4,290 2 7/16 49 4,400 2 1/2 49 4,30 2 1/16 49 4,400 2 1/2 49 4,30 2 1/16 49 4,400 2 1/2 49 4,30 2 1/16 49 4,30 2 2/16 49 4,30 2 2/16 40 4 4,400 2 1/2 40 4 4,400 2 1/2 40 4 4,400 2 1/2 41 4.1 4,510 2 9/16 42 4.2 4,600 2 5/8 2 1/4	07		770	7/16	3/8
10 1 1,100 5/8 11 1.1 1,210 11/16 12 1.2 1,220 3/k 5/8 13 1.3 1,3 1,430 13/16 14 1.4 1,540 7/8 3/4 15 1.5 1,550 15/16 7 16 1.6 1,760 1 1/16 18 1.8 1,980 1 1/8 1 19 1.9 2,090 1 3/16 20 2 2,200 1 1/8 21 2.1 2,310 1 5/16 1 22 2.2 2,420 1 3/8 23 2.3 2,530 1 7/16 1 1/4 24 2.4 2,640 1 1/2 25 2.5 2,750 1 9/16 1 3/8 26 2.6 2,860 1 5/8 27 2.7 2,970 1 11/16 28 2.8 3,080 1 3/4 1 1/2 29 2.9 3,190 1 13/16 30 3 3,3100 1 13/16 30 3 3,300 1 7/8 1 5/8 31 3.1 3,410 1 15/16 32 3.2 3,520 2 1 3/8 33 3.2 3,520 2 1/16 34 3.4 3,74 3,740 2 1/16 35 3.5 3,850 2 1/16 36 3.6 3,960 2 1/16 37 3.7 4,070 2 5/16 2 38 3.8 4,180 2 3/8 39 3.9 4,280 2 5/16 1 41 4.1 4,510 2 9/16 42 4.2 4,600 2 1/2 43 4.3 4,3 4,730 2 1/26 44 4,400 2 1/2 45 2/6 2 6,600 2 1/26 46 4,500 2 5/8 2 1/46 47 3,4 3,4 4,700 2 5/16 2 48 4,290 2 7/16 49 4,400 2 1/2 49 4,30 2 1/16 49 4,400 2 1/2 49 4,30 2 1/16 49 4,400 2 1/2 49 4,30 2 1/16 49 4,30 2 2/16 49 4,30 2 2/16 40 4 4,400 2 1/2 40 4 4,400 2 1/2 40 4 4,400 2 1/2 41 4.1 4,510 2 9/16 42 4.2 4,600 2 5/8 2 1/4		0.8		1/2	. /0
111	99	0.9	990	9/16	1/2
12 1.2 1,20 3/k 5/8  13 1.3 1,430 13/16  14 1.4 1,540 7/8 3/4  15 1.5 1,650 15/16  16 1.6 1,760 1  17 1.7 1,670 1 1/16  18 1.8 1,980 1 1/8 1  19 1.9 2,090 1 3/16  20 2 2,200 1 1/4  21 2.1 2,310 1 5/16 1 1/8  22 2.2 2,420 1 3/8  23 2.3 2,530 1 7/16 1 1/4  24 2.4 2,640 1 1/2  25 2.5 2,750 1 9/16 1 3/8  27 2.7 2,970 1 11/16  28 2.8 3,080 1 3/4 1 1/2  29 2.9 3,190 1 13/16  30 3 3,300 1 7/8 1 5/8  31 3.1 3,410 1 15/16  32 3.2 3,520 2  13/4 3,740 2 1/8  34 3,4 3,740 2 1/8  35 3.6 3,6 3,60 2 1/16  36 3.6 3,60 2 1/16  37 3.7 4,070 2 5/16 2  38 3.8 4,180 2 3/8  39 3.9 4,290 2 1/2  41 4,510 2 9/16  42 4,2 4,60 2 1/2  43 4,3 4,3 4,700 2 1/2  44 4,400 2 1/2  45 4,200 2 1/2  46 43 4,3 4,3 4,730 2 1/26  46 43 4,3 4,3 4,730 2 1/26  46 43 4,3 4,3 4,730 2 1/16  46 43 4,3 4,3 4,730 2 1/16  46 43 4,3 4,3 4,730 2 1/16  46 44 4,800 2 3/8  47 2 1/16  46 47 47 47 47 47 47 47 47 47 47 47 47 47			1,100	11/16	
13 1.3 1.430 13/16 14 1.4 1.540 7/8 3/4 15 1.5 1.650 15/16 7/8 16 1.6 1.760 1 1/16 18 1.8 1.980 1 1/8 1 19 1.9 2.990 1 3/16 20 2 2.200 1 1/4 21 2.1 2.310 1 5/16 1 1/8 22 2.2 2.400 1 3/8 23 2.3 2.530 1 7/16 1 1/4 24 2.4 2.640 1 1/2 25 2.5 2.750 1 9/16 1 3/8 26 2.6 2.6 2.650 1 5/8 27 2.7 2.970 1 11/16 28 2.8 3.080 1 3/4 1 1/2 29 2.9 3,190 1 13/16 20 2 1 3/8 1 1/2 21 2.1 2.1 2.310 1 5/16 1 1/4 22 3 2.3 2.530 1 7/16 1 1/4 24 2.4 2.650 1 1/2 25 2.5 2.750 1 9/16 1 3/8 26 2.6 2.6 2.650 1 5/8 27 2.7 2.970 1 11/16 28 2.8 3.080 1 3/4 1 1/2 29 2.9 3,190 1 13/16 20 3 3 3,200 1 7/8 1 5/8 31 3.1 3,140 1 15/16 32 3.2 3,520 2 1 3/4 33 3.3 3.630 2 1/16 34 3.4 3,740 2 1/8 35 3.5 3,850 2 3/16 1 7/8 36 3.6 3,60 2 1/4 37 3.7 4,070 2 5/16 2 39 3.9 4,290 2 7/16 40 4 4,600 2 1/2 41 4.1 4,510 2 9/16 42 4.2 4,620 2 5/8 2 1/4 43 4.3 4,3 4,730 2 1/16 43 4.3 4,3 4,730 2 1/16	11		1,210	11/10	E /Q
14 1.4 1.540 7/8 3/4  15 1.5 1.650 15/16 7/8  16 1.6 1.760 1 1/16 7/8  17 1.7 1.7 1.870 1 1/16 1  18 1.8 1.980 1 1/8 1  19 1.9 2.090 1 3/16  20 2 2.200 1 1/4  21 2.1 2.310 1 5/16 1 1/8  22 2.2 2.420 1 3/8  23 2.3 2.550 1 7/16 1 1/4  24 2.4 2.640 1 1/2  25 2.5 2.750 1 9/16 1 3/8  27 2.7 2.970 1 11/16  28 2.8 3.080 1 3/16  27 2.7 2.970 1 11/16  28 2.8 3.080 1 3/16  29 2.9 3.190 1 13/16  30 3 3.300 1 7/8 1 5/8  31 3.1 3,410 1 15/16  32 3.2 3.520 2 1/8  33 3.3 3.630 2 1/16  34 3.4 3.740 2 1/8  35 3.5 3.850 2 3/16 1 7/8  36 3.6 3.6 3.960 2 1/8  37 3.7 4.070 2 5/16 2  38 3.8 4.180 2 3/8  39 3.9 4.290 2 7/16  40 4 4.500 2 1/2  41 43 4.3 4.3 4.730 2 11/16  42 1/4 43 4.3 4.730 2 11/16  43 4.3 4.3 4.730 2 11/16  44 4.800 2 3/8  45 4.4 4.800 2 3/16	12		1,120	12/14	
16 1.6 1,760 1 1/16 17 1.7 1,870 1 1/16 18 1.8 1,980 1 1/8 1 19 1.9 2,090 1 3/16 20 2 2,200 1 1/4 21 2.1 2,10 1 5/16 1 1/8 22 2.2 2,420 1 3/8 23 2.3 2,500 1 7/16 1 1/4 24 2.4 2,640 1 1/2 25 2.5 2,750 1 9/16 1 3/8 26 2.6 2,860 1 5/8 27 2.7 2,970 1 11/16 28 2.8 3,080 1 3/4 1 1/2 29 2.9 3,190 1 13/16 20 3 3 3,300 1 7/8 1 5/8 31 3.1 3,410 1 15/16 32 3.2 3,520 2 1/8 33 3.3 3,630 2 1/16 34 3.4 3,740 2 1/8 35 3.5 3,850 2 3/16 1 7/8 36 3.6 3,960 2 1/8 37 3.7 4,070 2 5/16 2 38 3.8 4,180 2 3/8 39 3.9 4,290 2 7/16 40 4 4,600 2 1/2 41 4.1 4,510 2 9/16 42 4.2 4,620 2 5/8 2 1/4 43 4.3 4,730 2 11/16	13	٤٠٠	1,450	7/8	3/1
16 1.6 1,760 1 1/16 17 1.7 1,870 1 1/16 18 1.8 1,980 1 1/8 1 19 1.9 2,090 1 3/16 20 2 2,200 1 1/4 21 2.1 2,10 1 5/16 1 1/8 22 2.2 2,420 1 3/8 23 2.3 2,500 1 7/16 1 1/4 24 2.4 2,640 1 1/2 25 2.5 2,750 1 9/16 1 3/8 26 2.6 2,860 1 5/8 27 2.7 2,970 1 11/16 28 2.8 3,080 1 3/4 1 1/2 29 2.9 3,190 1 13/16 20 3 3 3,300 1 7/8 1 5/8 31 3.1 3,410 1 15/16 32 3.2 3,520 2 1/8 33 3.3 3,630 2 1/16 34 3.4 3,740 2 1/8 35 3.5 3,850 2 3/16 1 7/8 36 3.6 3,960 2 1/8 37 3.7 4,070 2 5/16 2 38 3.8 4,180 2 3/8 39 3.9 4,290 2 7/16 40 4 4,600 2 1/2 41 4.1 4,510 2 9/16 42 4.2 4,620 2 5/8 2 1/4 43 4.3 4,730 2 11/16	16		1,540	15/16	- 3/4
17	16-	1.6	1.760		7/8
18 1.8 1.980 1 1/8 1  19 1.9 2.090 1 3/15  20 2 2 2.200 1 1/4  21 2.1 2.3 10 1 5/16 1 1/8  22 2.2 2.4 2.0 1 3/8  23 2.3 2.5 30 1 7/16 1 1/4  24 2.4 2.6 1 1/2  25 2.5 2.790 1 9/16 1 3/8  26 2.6 2.6 2.6 0 1 5/8  27 2.7 2.970 1 11/16  28 2.8 3.080 1 3/4 1 1/2  29 2.9 3,190 1 13/16  30 3 3,190 1 17/8 1 5/8  31 3.1 3,410 1 15/16  32 3.2 3,520 2  1 3/4  33 3.3 3.6 30 2 1/16  34 3.4 3,740 2 1/8  35 3.5 3,850 2 3/16 1 7/8  36 3.6 3,960 2 1/8  37 3.7 4,070 2 5/16 2  38 3.8 4,180 2 3/8  39 3.9 4,290 2 7/16  40 4 4,400 2 1/2  41 4.1 4,510 2 9/16  42 4.2 4,620 2 5/8 2 1/4  43 4.3 4,3 4,730 2 11/16  44 4,400 2 1/2  45 4,40 2 5/16 2 1/4  47 4,400 2 1/2  48 4,400 2 1/2  49 4,400 2 1/2  40 4,400 2 1/2  41 4.1 4,510 2 9/16  42 4.2 4,620 2 5/18 2 1/4	17				170
19 1.9 2,090 1 3/16 20 2 2,200 1 1/4 21 2.1 2,310 1 5/16 1 1/8 22 2.2 2,420 1 3/8 23 2.3 2,530 1 7/16 1 1/4 24 2.4 2,640 1 1/2 25 2.5 2,790 1 9/16 1 3/8 26 2.6 2,660 1 5/8 27 2.7 2,970 1 11/16 28 2.8 3,080 1 3/4 1 1/2 29 2.9 3,190 1 13/16 30 3 3,300 1 7/8 1 5/8 31 3.1 3,410 1 15/16 32 3.2 3,520 2 1/16 32 3.2 3,520 2 1/16 33 3.3 3,630 2 1/16 34 3.4 3,740 2 1/8 35 3.5 3,850 2 3/16 1 7/8 36 3.6 3,66 3,960 2 1/8 37 3.7 4,070 2 5/16 2 38 3.8 4,180 2 3/8 39 3.9 4,290 2 7/16 40 4 4,500 2 1/2 40 41 4,500 2 1/2 41 41,510 2 9/16 42 4.2 4,620 2 5/8 2 1/4	18		1.980	1 1/8	1
20 2 2,200 1 1/h 21 2.1 2,310 1 5/16 1 1/8 22 2.2 2,420 1 3/8 23 2.3 2,530 1 7/16 1 1/4 24 2.4 2,640 1 1/2 25 2.5 2,750 1 9/16 1 3/8 26 2.6 2,660 1 5/8 27 2.7 2,970 1 11/16 28 2.8 3,080 1 3/h 1 1/2 29 2.9 3,190 1 13/16 30 3 3,100 1 7/8 1 5/8 31 3.1 3,410 1 15/16 32 3.2 3,520 2 1 3/h 34 3.4 3,740 2 1/16 35 3.5 3,850 2 3/16 1 7/8 36 3.6 3,630 2 1/16 37 3.7 4,070 2 5/16 2 38 3.8 4,180 2 3/8 39 3.9 4,290 2 7/16 40 4 4,400 2 1/2 41 4.1 4,510 2 9/16 42 4.2 4,600 2 5/8 2 1/4 43 4,3 4,3 4,730 2 1/16	19			1 3/16	
21	20 .		2,200	1 1/4	
22 2.2 2,420 1 3/8 23 2.3 2,520 1 7/16 1 1/4 24 2.4 2,640 1 1/2 25 2.5 2,750 1 9/16 1 3/8 26 2.6 2,66 1 5/8 27 2.7 2,970 1 11/16 28 2.8 3,080 1 3/4 1 1/2 29 2.9 3,190 1 13/16 30 3 3,300 1 7/8 1 5/8 31 3.1 3,410 1 15/16 32 3.2 3,520 2 1 1/6 33 3.3 3,600 2 1/16 34 3.4 3,740 2 1/8 35 3.5 3,850 2 3/16 1 7/8 36 3.6 3,66 3,960 2 1/8 37 3.7 4,070 2 5/16 2 38 3.8 4,180 2 3/8 39 3.9 4,290 2 7/16 40 4 4,400 2 1/2 41 41 4,510 2 9/16 42 4.2 4,660 2 5/8 2 1/4 43 4,3 4,3 4,730 2 11/16 44 4,840 2 3/4	21		2,310	1 5/16	1 1/8
23 2.3 2.530 1 7/16 1 1/4 24 2.4 2.640 1 1/2 25 2.5 2.5 2,750 1 9/16 1 3/8 26 2.6 2.8 3,080 1 3/4 1 1/2 28 2.8 3,080 1 3/4 1 1/2 29 2.9 3,190 1 13/16 30 3 3,100 1 7/8 1 5/8 31 3.1 3,410 1 15/16 32 3.2 3,520 2 1 3/4 32 3.2 3,520 2 1 3/4 33 3.3 3,630 2 1/16 34 3.4 3,740 2 1/8 35 3.5 3,850 2 3/16 1 7/8 36 3.6 3,960 2 1/4 37 3.7 4,070 2 5/16 2 38 3.8 4,180 2 3/8 39 3.9 4,290 2 7/16 40 4 4,400 2 1/2 41 4.1 4,510 2 9/16 42 4.2 4,620 2 5/8 2 1/4 43 4.3 4,3 4,730 2 11/16	22	2.2	2,420	1 3/8	
24 2.4 2,640 1 1/2 25 2.5 2,750 1 9/16 1 3/8 26 2.6 2,860 1 5/8 27 2.7 2,970 1 11/16 28 2.8 3,080 1 3/4 1 1/2 29 2.9 3,190 1 13/16 30 3 3,300 1 7/8 1 5/8 31 3.1 3,410 1 15/16 32 3.2 3,520 2 1 3/4 33 2.3 3,630 2 1/16 34 3.4 3,740 2 1/8 35 3.5 3,850 2 3/16 1 7/8 36 3.6 3,960 2 1/8 37 3.7 4,070 2 5/16 2 38 3.8 4,180 2 3/8 39 3.9 4,290 2 7/16 40 4 4,500 2 1/2 40 4 1,510 2 9/16 41 4.1 4,510 2 9/16 42 4.2 4,620 2 5/8 2 1/4	23	2.3	2,530	1 7/16	1 1/4
27 2.7 2.970 111/16 28 2.8 3,080 1 3/4 1 1/2 29 2.9 3,190 1 13/16 30 3 3,300 1 7/8 1 5/8 31 3.1 3,410 1 15/16 32 3.2 3,520 2 1 3/4 33 3.3 3,630 2 1/16 34 3.4 3,740 2 1/8 35 3.5 3,850 2 3/16 1 7/8 36 3.6 3,960 2 1/8 37 3.7 4,070 2 5/16 2 38 3.8 4,180 2 3/8 39 3.9 4,290 2 7/16 40 4 4,500 2 1/2 40 4 4,500 2 1/2 41 4.1 4,510 2 9/16 42 4.2 4,620 2 5/8 2 1/4 43 4,3 4,3 4,730 2 11/16 44 4,840 2 3/8	24	2.4	2,640		
27 2.7 2.970 111/16 28 2.8 3,080 1 3/4 1 1/2 29 2.9 3,190 1 13/16 30 3 3,300 1 7/8 1 5/8 31 3.1 3,410 1 15/16 32 3.2 3,520 2 1 3/4 33 3.3 3,630 2 1/16 34 3.4 3,740 2 1/8 35 3.5 3,850 2 3/16 1 7/8 36 3.6 3,960 2 1/8 37 3.7 4,070 2 5/16 2 38 3.8 4,180 2 3/8 39 3.9 4,290 2 7/16 40 4 4,500 2 1/2 40 4 4,500 2 1/2 41 4.1 4,510 2 9/16 42 4.2 4,620 2 5/8 2 1/4 43 4,3 4,3 4,730 2 11/16 44 4,840 2 3/8	25	2.5	2,750	1 9/16	1 3/8
26 2.8 3,080 1 3/h 1 1/2 29 2.9 3,190 1 13/16 30 3 3,300 1 7/8 1 5/8 31 3.1 3,110 1 15/16 32 3.2 3,520 2 1 3/h 33 3.3 3,630 2 1/16 34 3.4 3,740 2 1/8 35 3.5 3,850 2 3/16 1 7/8 36 3.6 3,960 2 1/h 37 3.7 1,070 2 5/16 2 38 3.8 1,180 2 3/8 39 3.9 1,290 2 7/16 10 1 1,510 2 9/16 11 1 1,510 2 9/16 12 1,600 2 5/18 2 1/h 13 1,3 1,3 1,730 2 11/16 14 1,510 2 9/16 15 1,600 2 5/18 2 1/h 16 1,510 2 9/16 16 1,510 2 9/16 17 17 18 18 18 18 18 18 18 18 18 18 18 18 18	26		2,860	1 5/8	
29 2.9 3,190 1 13/16 30 3 3,300 1 7/8 1 5/8 31 3.1 3.1 3,410 1 15/16 32 3.2 3,520 2 1 3/4 33 3.3 3,630 2 1/16 34 3.4 3,740 2 1/8 35 3.5 3,850 2 3/16 1 7/8 36 3.6 3,960 2 1/4 37 3.7 4,670 2 5/16 2 38 3.8 4,180 2 3/8 39 3.9 4,290 2 7/16 40 4 4,400 2 1/2 40 4 4,400 2 1/2 40 4 4,400 2 1/2 41 4,11 4,510 2 9/16 42 4.2 4,620 2 5/8 2 1/4 43 4.3 4,3 4,730 2 11/16 44 4,840 2 3/4	27			1 11/16	
30         3         3,300         1 7/8         1 5/8           31         3.1         3,410         1 15/16         1 3/4           32         3.2         3,520         2         16         1 3/4           33         3.3         3,630         2 1/16         1 3/4         1 7/8           34         3.4         3,740         2 1/8         1 7/8			3,080	1 3/4	1 1/2
33 2.3 3.630 2 1/16  34 3.4 3.7 <sup>1</sup> 00 2 1/8  35 3.5 3.850 2 3/16 1 7/8  36 3.6 3.950 2 1/4  37 3.7 4,070 2 5/16 2  38 3.8 4,180 2 3/8  39 3.9 4,290 2 7/16  40 4 4,400 2 1/2  41 4.1 4,510 2 9/16  42 4.2 4,620 2 5/8 2 1/4  43 4.3 4,730 2 11/16  44 4,800 2 3/8	29	2.9	3,190	1 13/16	/0
33 2.3 3.630 2 1/16  34 3.4 3.7 <sup>1</sup> 00 2 1/8  35 3.5 3.850 2 3/16 1 7/8  36 3.6 3.950 2 1/4  37 3.7 4,070 2 5/16 2  38 3.8 4,180 2 3/8  39 3.9 4,290 2 7/16  40 4 4,400 2 1/2  41 4.1 4,510 2 9/16  42 4.2 4,620 2 5/8 2 1/4  43 4.3 4,730 2 11/16  44 4,800 2 3/8	30			1 7/8	1 5/0
33 2.3 3.630 2 1/16  34 3.4 3.7 <sup>1</sup> 00 2 1/8  35 3.5 3.850 2 3/16 1 7/8  36 3.6 3.950 2 1/4  37 3.7 4,070 2 5/16 2  38 3.8 4,180 2 3/8  39 3.9 4,290 2 7/16  40 4 4,400 2 1/2  41 4.1 4,510 2 9/16  42 4.2 4,620 2 5/8 2 1/4  43 4.3 4,730 2 11/16  44 4,800 2 3/8	31		3,410	1 13/10	1 2/6
34 3.4 3,740 2 1/8 35 3.5 3,850 2 3/16 1 7/8 36 3.6 3,960 2 1/4 37 3.7 4,070 2 5/16 2 38 3.8 4,180 2 3/8 39 3.9 4,290 2 7/16 40 4 4,500 2 1/2 41 4.1 4,510 2 9/16 42 4.2 4,660 2 5/8 2 1/4 43 4.3 4,730 2 11/16 44 4,840 2 3/8	. 32	3.2	3,720	2 1/16	1 3/4
35 3.5 3,850 2 3/16 1 7/8 36 3.6 3,960 2 1/4 37 3.7 4,070 2 5/16 2 38 3.8 4,180 2 3/8 39 3.9 4,290 2 7/16 40 4 4,500 2 1/2 41 4,510 2 9/16 42 4.2 4,620 2 5/8 2 1/4 43 4,3 4,730 2 11/16 44 4,840 2 3/4	<del>37</del>	3.3	3,030	2 1/8	
36 3.6 3.960 2 1/4 37 3.7 4,070 2 5/16 2 38 3.8 4,180 2 3/8 39 3.9 4,290 2 7/16 40 4 4,800 2 1/2 41 4.1 4,510 2 9/16 42 4.2 4,620 2 5/8 2 1/4 43 4.3 4,730 2 11/16 44 4,800 2 3/4	35	3. <del>4</del>	3,140	2 2/16	1.7/8
37 3.7 4,070 2 5,16 2 38 3.8 4,180 2 3,8 39 3.9 4,290 2 7/16 40 4 4,500 2 1/2 41 4,510 2 9/16 42 4.2 4,620 2 5/8 2 1/4 43 4.3 4.730 2 11/16 44 4.1 4.840 2 3/4	36	3.6	3,060	2 1/4	- 1/-
h1 4.1 4,510 2 9/16 h2 4.2 4,620 2 5/8 2 1/4 h3 4.3 4,730 2 11/16 hh h, h, sho 2 3/h	37			2 5/16	2
h1 4.1 4,510 2 9/16 h2 4.2 4,620 2 5/8 2 1/4 h3 4.3 4,730 2 11/16 hh h, h, sho 2 3/h	38	3.8	4.180	2 3/8	-
h1 4.1 4,510 2 9/16 h2 4.2 4,620 2 5/8 2 1/4 h3 4.3 4,730 2 11/16 hh h, h, sho 2 3/h	30	3.9	4,290	2 7/16	
h1 4.1 4,510 2 9/16 h2 4.2 4,620 2 5/8 2 1/4 h3 4.3 4,730 2 11/16 hh h, h, sho 2 3/h	40	<del>- 4</del> -	4.400	2 1/2	
42 4.2 4,620 2 5/8 2 1/4 43 4.3 4,730 2 11/16 bh h.h h.840 2 3/4		4.1	4,510	2 9/16	
կ3 4.3 4,730 2 11/16 հե եր երհ հ.840 2 3/4	42	4.2	4,620	2 5/8	2 1/4
հե եւև և,Ց40 2.3/4		4.3	4,730	2 11/16	
45 4.5 4,950 2 13/16			4,840	2 3/4	
	45	4.5	4,950	2 13/16	<del></del>

#### Code 4. continued Statute

figure	Km	(Approx.)	(Approx.)	(Approx.)
46	4.6	5,060	2 7/8	2 1/2
47	4.7	5,170 5,280	2 15/16	•
<u>1</u> 8	4.8	5,280	3	
49	4.9	5,390 5,500	3 1/16	
50	5	5,500	3 1/8	
51;				
52				
25		HOT USED		
25				
52 53 54 55 56	- 6	6,600	3 3/1	3
57	7	7,700	4 3/8	,
쇎	á	8,800	Z 3/0	4 .
57 58 59 60	<del>- j</del>	9,900	5 5 5/8 6 1/4 6 7/8	5
60	10	11,000	6 1/4	•
61 62	11	12,100	6 7/8	6
62	12	12,100 13,200	7 1/2	
63	13	14,300	A 1/A	7
64	14	15,400	A 2/h	
63 64 65 66 67	15	14,300 15,400 16,500	9 3/8	- 8
66	16	17,600	10	
67	17	18,700	10 5/8	9
68 69	18	19,800	11. 1/4 11. 7/8	10
<u>70</u>	19 20	20,900 22,000	11 7/8 12 1/2	11
71	21	23,100	13 1/8	
72	22	24,200	13 3/4 14 3/8	12
73 74	23 24	25,300 26,400	15	13
75	25	27,500	īś 5/8	13
76	25 26	28,600	16 1/4	14
76 77 78	27 26	29,700	16 7/8	
78	28	30,800	17 1/2 18 1/8	15
79	29	31,900	18 1/8	-
79 80 81	30	33,000	18 3/4	
81	35		21 7/8	20
82 83	40 45		25 28 1/8	_
84 84	47 50		28 1/8 31 1/4	25
Ar.	20		31 1/4 34 3/8	
85 86	50 55 60		37 1/2	30
87	65		40 5/8	25
87 88	70		43 3/4	35
89 90	> 70 < 0.05			> 35
90	< 0.05	<55	21/32	< 50 yards
91	0.05	55 220	1/32	50 yards
92	0.2	220	1/8	200 yarda
93	0.5	550	5/16	1/4
94	1	1,100	5/8	1/2
91 92 93 94 95 96	<u>2</u>	2,200	2/32 1/32 1/8 5/16 5/8 1 1/4	1
90 97	10	4,400 11,000	2 1/2 6 1/4	2
SI Ao	20	22,000	12 1/2	5 10
<u>98</u> 99	≥ 50	≥ 55,000	<u>≥ 31 1/4</u>	> 25
		- ///		≥ 25
otes:				

- (1) The code is direct reading in units of 100 m (approx. 110 yards or 1/16 statute mile) from 0 to 50.
- (2) The code figures 51 to 55 are not used.
- (3) For code figures 56 to 80, 50 is subtracted and the remaining figure is direct reading in units of km (approx. 1,100 yards or 5/8 statute mile).
- (4) For code figures 81 to 89, the code reads in increments of 5 km (3 1/8 statute miles) from the values given for code figure 80.
- (5) The code table is to be considered as a coding device in which certain code figures are assigned values. These are discrete values (not ranges). Any observation or forecast of values to be coded in the code table is to be made without regard to the code table. The coding is then accomplished according to the following rule: If the observed or forecast visi-bility is between two of the reportable distances as given in the table, the code figure for the lower reportable distance is reported.

### Code 1 (1949 WMO Code 70) (1960 WMO Code 3300)

#### Q - Octant Of The Globe

North Latitude 00°00'-90°00'N	South Latitude 00°01'-90° 00'
Octant Longitude Limits  Off 00°00'W - 89°59'W  1# 90°00'W - 179°59'W  2 179°59'E - 90°00'E  3 89°59'E - 00°01'E	Octant Longitude Limits  5# 00°00'W - 89°59!W 6# 90°00'W - 179°59!W 7 179°59'E - 90°00'E 8 89°59'E - 00°01'E

- # When a ship is: a) exactly at 00°00' Longitude it will be considered to be in Octant 0 or 5 depending on the Latitude.
- b) exactly at 180°00' Longitude it will be considered to be in Octant 1 or 6 depending on the Latitude.


Variable

### Code 5

### (1949 WMO Code 92) (1960 WMO Code 4677)

- ww 00 49 No precipitation at the station at the time of observation
- ww 00 19 No precipitation, fog, ice fog (except 11 and 12), duststorm, sandstorm, drifting or blow-ing snow at the station (land station or ship) at the time of observation or, except for 09 and 17, during the preceding hour.

Code figure



- 03 Clouds generally forming
- (04 Visibility reduced by smoke, e.g. weldt or forest fires, industrial smoke or volcanic
- 06 Widespread dust in suspension in the air, not raised by wind at or near the station at the
- Dust or sand raised by wind at or near the station at the time of observation, but no well developed dust whirl(s) or sand whirl(s). and no dustatorm or sandatorm seen
- Well developed dust whirl(s) or sand whirl(s) seen at or near the station during the preceding hour or at the time of observation, but no duststorm or sandstorm
- (09 Duststorm or sandstorm within sight at the time of observation, or at the station during the preceding hour
- 10 Mist
- 11 (Patches of ) shallow fog or ice fog at the station, whether on land or sea, not deeper than about 2 metres on land or 10 metres at sea (continuous )
- 13 Lightning visible, no thunder heard
- 14 Precipitation within sight, not reaching the ground or the surface of the sea
- 15 Precipitation within sight, reaching the ground or the surface of the sea, but distant (i.e. estimated to be more than 5 km) from the
- 16 Precipitation within sight, reaching the ground or the surface of the sea, near to, but not at the station
- 17 Thunderstorm, but no precipitation at the time of observation
- 18 Squalls at or within sight of the station during the pre-19 Funnel cloud(s)
  - ceding hour or at the time (tornedo cloud or) of observation waterspout)

### Code 5, continued

not falling

ns shower(s)

ww 20 - 29 Precipitation, fog, ice fog or thunderstorm at the station during the preceding hour but not at the time of observation

Code figure

- 20 Drizzle (not freezing) or 21 Rain (not freezing)
- 23 Roin and snow or ice pellets, type (a)
- 24 Freezing drizzle or freezing rain
- 25 Shower(s) of rain
- 26 Shower(s) of snow, or of rain and anov
- 27 Shower(s) of hail(ice pellets, type (b), snow pellets), or of rain and hail (ice pellets, type (b), snow pellets)
- 26 For or ice for
- 29 Thunderstorm (with or without precipitation)
- ww 30 39 Duststorm, sandstorm, drifting or blowing

has decreased during the preceding 31) Slight or moderate dust no appreciable storm or sandstorm change during the preceding hour has been or has increased during the preceding hour

has decreased dur-33) ing the preceding no appreciable Severe dustators or exodetore change during the preceding hour has begun or has

increased during the preceding hour 36 Slight or moderate generally low drifting snov

(below eye level) 37 Heavy drifting snow

38 Slight or moderate generally high (above eye level) blowing snow 39 Heavy blowing snow

ww 40 - 40 Fox or ice fox at the time of observation

40 Fog or ice fog at a distance at the time of observation, but not at the station during the preceding hour, the fog or ice fog extending to a level above that of the observer

### Code 5, continued

## Code figure

- 42 Fog or ice fog, sky visible ) has become thinner during the 43 Fog or ice fog, sky invisible) preceding hour
- I Fog or ice fog, sky visible ) no appreciable 45 Fog or ice fog, sky invisible) the preceding

1 Fog or ice fog in patches

- 46 Fog or ice fog, sky visible ) has been or her become thicker 47 Fog or ice fog, sky invisduring the pre-
- ceding hour 48 Fog, depositing rime, sky visible
- 49 Fog, depositing rime, sky invisible ww 50 - 99 Precipitation at the station at the time of observation
- ww 50 59 Drissle
  - 50 Drizzle, not freezing, intermittent
  - slight at time of observation 51 Drissle, not freezing, cont.immeue
  - 52 Drissle, not freezing, intermittent moderate at time of observation 53 Drissle, not freezing,
  - continuous Drizzle, not freezing, intcomittent
  - heavy(dense) at time of observation 55 Driszle, not freezing, continuous
  - 56 Drissle, freezing, slight
  - 57 Drizzle, freezing, moderate or heavy (dense)
  - 53 Drissle and rain, slight
  - 39 Drizzle and rain, moderate or heavy
- - Main, not freezing, slight at time of observation 61 Main, not freezing, continuous
  - 62 Main, not freezing, intermittent
  - moderate at time of observation 63 Main, not freezing, contimous
  - 64 Hain, not freezing, intermittent heavy at time of 65 Rain, not freezing,
  - 66 Rain, freezing, slight
  - 67 Main, freezing, moderate or beavy
  - 68 Main or drissle and snow, slight
  - 65 main or drizzle and snow, moderate or heavy

### Code 5, continued

- ww 70 79 Solid precipitation not in showers
- - 70 Intermittent fall of snow flakes) slight at
  - 71 Continuous fall of snow flakes ) observation
  - 72 Intermittent fall of snow flakes) moderate at 73 Continuous fall of snow flakes
- 74 Intermittent fall of snow flakes) heavy at
- time of 75 Continuous fall of snow flakes ) observation
- 76 Ice prisms (with or without fog)
- 77 Snow grains(with or without fog)
- 78 Isolated starlike snow crystals (with or with-
- 79 Ice pellets, type (a)
- ww 80 99 Showery precipitation, or precipitation with current or recent thunderstorm
  - 80 Rain shower(s), alight
  - 81 Rain shower(s), moderate or heavy
  - 82 Rain shower(s), violent
  - 83 Shower(s) of rain and snow mixed, slight
  - 84 Shower(s) of rain and snow mixed, moderate or
  - 85 Snow shower(s), slight
  - 86 Snow shower(s), moderate or heavy
  - 87) Shower(s) of snow pellets or ice) slight
    ) pellets, type(b), with or without)
    88) rain or rain and snow mixed ) moderate moderate or
  - 89 Shower(s) of hail, with or
  - without rain or rain and anow 90 mixed, not associated with moderate or
  - 91 Slight rain at time of observa-
  - 92 Moderate or heavy rain at time of observation
  - 93 Slight snow, or rain and snow mixed or hail (ice pellets, type (b), snow pellets), at time of
  - 94 Moderate or heavy snow, or rain and snow mixed or hall (ice pellets, type(b), snow pellets) at time of observa-
  - 95 Thunderstorm, slight or moderste, without hail (ice pellets, type (b), snow pellets);but with rain and/or snow at time of observation
  - 96 Thunderstorm, slight or moderate, with hall (ice pellets, type (b), snow pellets) at

thundaretown

aliant

thunderstore

hour but not

during the

preceding

at time of

### Code 5. continued

- 97 Thunderstorm, heavy, without hail (ice pellets, type(b), snow pellets), but with rain and/or snow at time of obser-
- 98 Thunderstorm combined with time of observation
- 99 Thurderstorm, heavy, with hall (ice pellets, type(b), snow pellets) at time of observation

### Code 6 (1949 WMO Code 90) (1960 WMO Code 4500)

#### W - Past weather

#### Code figure

- Cloud covering 1/2 or less of the sky throughout the appropriate period
- I Cloud covering more than 1/2 of the sky during part of the appropriate period and covering 1/2 or less during part of the period
- Cloud covering more than 1/2 of the sky throughout
- Sandstorm, duststorm or blowing snow
- Fog or ice fog or thick haze
- Drizzle
- Snow, or rain and snow mixed
- Thunderstorm(s) with or without precipitation

- (1) In the case of a sandstorm, with a temperature below O°C, the word SANDSTORN is added at the end of the report, but is omitted in punching.
- (2) In the case of a shower or a thunderstorm, accompanied by hail, the words PAST HAIL are added at the end of the report, but are omitted in punching.
- (3) In the case of a snow shower or a shower of rain and snow mixed, with a temperature above O°C, the word DHOW or SLEET is added at the end of the report, but is omitted in punching.

### Code 7

### (1949 WMO Code 11) (1960 WMO Code 0513)

Cr - Clouds of the genera Stratocumilus, Stratus, Cumilus

#### Non technical specifications

- O No Stratocumilus, Stratus, Cumilus or Cumilonimbus
- 1 Cumulus with little vertical extent and seemingly flattened, or ragged Cumulus other than of bad
- 2 Cumulus of moderate or strong vertical extant. generally with protuberances in the form of domes or towers, either accompanied or not by other Cumulus or by Stratocumulus, all having their bases at the same
- Cumulonimbus the summits of which, at least partially, lack sharp outlines, but are neither clearly fibrous (cirriform) nor in the form of an anvil: Cumulus. Street committee on Street as may also he present
- Stratocumulus formed by the spreading out of Cumulus: Complete may also be present
- Stratocumulus not resulting from the spreading out of
- 6 Stratus in a more or less continuous sheet or layer, or in ragged shreds, or both, but no Stratus fractus of
- 7 Stratus fractus of bad weather (generally existing during precipitation and a short time before and after), or Cumulus fractus of bad weather, or bota (pannus), usually below Altostratus or Nimbostratus
- 8 Complus and Stratocumulus other than that formed from the spreading out of Cumulus; the base of the Cumplus is at a different level from that of the
- Cumulonimbus, the upper part of which is clearly fibrous (cirriform), often in the form of an anvil; either accompanied or not by Cumulonimbus without anvil or fibrous upper part, by Cumulus, Stratocumulus, Stratus or pannus
- X Stratocumilus, Stratus, Cumulus and Cumulonimbus invisible owing to darkness, fog, blowing dust or sand, or other similar phenome

### Code 8 (1949 WMO Code 43) (1960 WMO Code 1600)

h = Height above Ground of the Base of the Cloud

Code	(em rece)	
Figure	Height in Feet	Height in Meters
0	0- 149	0- 49
1	150- 299	50 99
2	300- 599	100- 199
3	600 999	200- 299
4	1,000-1,999	300- 599
5	2,000-3,499	600- 999
6	3,500-4,999	1,000-1,499
7	5,000-6,499	1,500-1,999
8	6,500-7,999	2,000-2,499
9	8,000 or higher, or	2,500 or higher, or

Note: The heights (in feet) given in this code table approximately correspond to those given in 1949 and 1955 WMO Code 43 and 1960 WMO Code 1600 and those given in the ninth decade (i.e., code figures 90-99) of 1949 and 1955

## Code 9 (1949 WMO Code 12) (1960 WMO Code 0515)

C. - Clouds of the genera Altocumulus. Altostratus and

### figure

- No Altocumulus, Altostratus or Nimbostratus
- Altostratus, the greater part of which is semitransparent; through this part the sun or moon mov he weakly visible, as through ground glass
- Altostratus, the greater part of which is sufficiently dense to hide the sum or moon.
- Altocumulus, the greater part of which is semitransparent; the various elements of the cloud change only slowly and are all at a single
- Patches (often in the form of almonds or fishes) of Altocumulus, the greater part of which is semi-transparent; the clouds occur at one or more levels and the elements are continually changing in appearance
- Semi-transparent Altocumulus in bands, or Altocumulus in one or more fairly continuous layers (semi-transparent or opaque), progressively invading the sky: these Altocumulus clouds generally thicken as a whole
- Altocumulus resulting from the spreading out of Cumulus (or Cumulonimbus)
- Altocumulus in two or more layers.usually opaque in places, and not progressively invading the sky; or opaque layer of Altocumulus, not progressively invading the sky; or Altocumulus together with Altostratus or Nimbostratus
- Altocumulus with anyoutings in the form of small towers or battlements, or Altocumulus having the appearance of cumuliform tufts
- Altocumulus of a chaotic sky, generally at
- Altocumulus, Altostratus and Nimbostratus invisible owing to darkness, fog, blowing dust or sand or other similar phenomena, or more often because of the presence of a continuous layer of lower clouds

### Code 10

### (1949 WMO Code 13) (1960 WMO Code 0509)

Cu - Clouds of the genera Cirrus, Cirrocumulus and Cirrostratus

#### Non technical specificacions figure

- No Cirrus Cirrocumulus or Cirrostratus
- Cirrus in the form of filaments, strands or hooks, not omoressively invading the sky
- Dense Cirrus, in natches or entangled sheaves, which usually do not increase and sometimes seem to be the remains of the upper part of a Cumulonimbus; or Cirrus with sproutings in the form of small turrets or battlements, or Cirrus having the appearance of cumuliform
- Dense Cirrus, often in the form of an anvil, being the remains of the upper parts of Cumulonimbus
- Cirrus in the form of hooks or of filaments, or both, progressively invading the sky; they generally become denser as a whole
- Circusoften in hands converging towards one point or two opposite points of the horizon)and Cirrostratus. or Cirrostratus alone; in either case, they are progressively invading the sky, and generally growing denser as a whole, but the continuous weil does not reach 45 degrees above the horizon
- Cirrus(often in bands converging towards one point or two opposite points of the horizon) and Cirrostratus, or Cirrostratus alone: in either case. they are progressively invading the sky, and generally growing denser as a whole; the continuous weil extends more than 45 degrees above the horizon, without the sky being totally covered
- Veil of Cirrostratus covering the celestial dome
- Cirrostratus not progressively invading the sky and not completely covering the celestial dome
- Cirrocumulus alone, or Cirrocumulus accompanied by Cirrus or Cirrostratus, or both, but Cirrocumulus is predominant
- Cirrus.Cirrocumulus and Cirrostratus invisible owing to darkness, fog, blowing dust or sand or other similar phenomena, or more often because of the pres-. ence of a continuous layer of lower clouds

# Code 11 (1949 WMO Code 23B) (1960 WMO Code 0885)

Code Figure		Code Figure	
00 01 02 03 04 05 06 07 08 09 10 11 12 13 14 15 16	Calm (no veres) 5° - 11° 15° - 24° 25° - 34° 35° - 44° 35° - 64° 65° - 74° 75° - 64° 65° - 104° 105° - 114° 115° - 124° 125° - 134° 135° - 144° 155° - 164° 155° - 164° 155° - 164° 155° - 164° 155° - 164°	19 20 21 22 22 23 25 25 27 28 29 30 32 33 35 35 39 29 29	185" - 194" 195" - 204" 205" - 214" 215" - 224" 225" - 234" 255" - 234" 255" - 254" 255" - 254" 255" - 264" 255" - 264" 255" - 264" 255" - 294" 255" - 394" 255" - 394" 315" - 324" 315" - 334" 315" - 344" 315" -

# Code 13 (1949 WMO Code 42) (1960 WMO Code 1555) E. - Nean Maximum Relight of the Vaves

Code Figure *	) / **)	If :	50 is added to dudy
0	Less than 1/4 m (1 ft) 1/2 m (1 1/2 ft)	0	5 = (16 ft) 5 1/2 = (17 1/2 ft)
ĭ.	1/2 = (11/2 ft)	1	5 1/2 m (17 1/2 ft)
2	1 2 (3 (4)	2	6 m (19 ft)
•	11/0= ) = (4)	3	61/2 = (21 ft)
2	1 1/2 m ( 5 ft) 2 m ( 6 1/2 ft)	Ĭ.	6 1/2 = (21 ft) 7 = (22 1/2 ft)
•	2 / 2 / 2 / 2 / 2 / 2 / 2 / 2 / 2 / 2 /	5	7 1/2 m (24 ft)
2	2 1/2 = (8 ft)	ź	8 = (25 1/2 ft)
6	3 a (91/2 ft)	2	8 1/0 = (27 7 4)
7	3 1/2 m (11 ft)	1	8 1/2 = (27 ft)
8	4 m (13 ft)	8	9 , 1 29 , 16
ā	3 1/2 = (11 ft) 4 = (13 ft) 4 1/2 = (14 ft)	9	9 1/2 m (29 ft) 9 1/2 m (30 1/2 ft)

- e) Each code figure provides for reporting a range of heights. For example: 1 = 1/k m (1 ft) to 3/k m (2 1/2 ft); 5 = 2 1/k m (7 ft) to 2 3/k m (9 ft); 9 = k 1/k m (13 1/2 ft) to 4 3/4 m (15 ft), etc.
- . 40) If a wave height comes exactly midway between the heights corresponding to two code figures, the lower code figure should be reported.

# Code 12 (1949 WMO Code 69) (1960 WMO Code 3155)

P - Period of Waves

Code Figure		Code Figure	
2 3 4 5 6 7	5 seconds or less 6 or 7 seconds 8 or 9 seconds 10 or 11 seconds 12 or 13 seconds 14 or 15 seconds	8 9 0 1 / cr x	16 or 17 seconds 18 or 19 seconds 20 or 21 seconds Over 21 seconds Calm, or period not determined

- Notes:
  (1) The period of the waves is the time between the passage of two successive wave crests past a fixed point (it is equal to the wave length divided by the wave speed).
- (2) The average value of the wave period is reported, as obtained from the larger well-formed waves of the wave system being observed.

LIST OF NUMBERS INDICATING THE COUNTRY OF ORIGIN OF THE INTERNATIONAL MARITIME METEOROLOGICAL PUNCE CARD

.00	Netherlands	17	Japan
01	Norway	18	Pakistan
02	USA	19	Argentina
	United Kingdom		Sweden
	France	21	Federal Republic of Germany
	Demark		Iceland
	Italy		Israel
	India		Halaysia
21	THUIS		USSR
	Hong Kong	25	
09	New Zealand		Finland
10	Ireland	27	Korea New Caledonia
11	Philippines	28	New Caledonia
	United Arab Republic	29	Portugal ·
	Canada		Spain
	Belgium	ŭ	Thailand
	South Africa		Yugoslavia
-3	DOUGH ALFAUR		T #6
16	Australia	33	
		33 34	Brasil